

# X-Series Video Servers

Wavestore X-Series Video Servers deliver an enterprise recording, management and control solution for large size projects that demand mission-critical reliability.



Up to 254 network cameras can be connected to each video server, which are supplied with pre-installed Wavestore's Video Management Software (VMS). Throughput options up to 2,400Mbps/sec are available, with multiple network interfaces to segregate incoming and outgoing network traffic. Ports can be bonded to provide fault-tolerance and maintain high performance at all times.

Housed in a rack mountable 4U case, X-Series Video Servers come complete with dual power supply as standard and can accommodate up to 24 x 3.5" hot swappable hard drives to provide up to 240TB of storage. This can deliver more than 48 days continuous real-time recording from 254 Full HD cameras with RAID5 redundancy\*\*.

## Choose your Wavestore VMS channel license level

X-Series Video Servers are compatible with all four levels of Wavestore's VMS: Base, Premium, Enterprise and Ultimate, which offer a broad range of capabilities and features to ensure the right solution for any given application.

## Server Groups

Multiple X-Series Video Servers, as well as other Wavestore video servers, NVRs and HVRs, can be configured into a server group of up to 255 units\* to satisfy large and distributed installations via a single Graphical User Interface (GUI).

## Failover

X-Series Video Servers are failover ready and can be used to protect your live viewing, recorded data and configuration in the event of hardware failure on a primary server. Should this occur, the failover server will automatically take the place of the primary server by applying the same configuration and continuing to display and record video, all without any operator intervention. Failover is available at Wavestore VMS Enterprise channel license level and above.

## HyperRAID™ redundancy and EcoStore™ energy saving

X-Series Video Servers are compatible with Wavestore's HyperRAID™ technology as standard, providing options of RAID5/RAID6 (N+1/N+2) at Wavestore VMS Premium or Enterprise channel license levels, or up to an industry leading N+5 at Ultimate channel license level. EcoStore™ is also provided at Enterprise channel license level and above, which can save over 80% of HDD energy by spinning down drives not in a read or write state.

## Warranty

All X-Series Video Servers are supplied with a full three-year return to base hardware warranty, extendable to five-years.

## Pre-installed with Wavestore Video Management Software (VMS)

Whether you are looking for a video only application using a mix of camera technologies, including 360° fisheye and 4K, or a fully integrated solution with third-party providers for Access Control, Video Analytics, Intruder Detection and more, it is possible to create best-in-breed total security solutions that meet exacting specifications for the end-customer with Wavestore's ONVIF conformant truly open-platform VMS.

Coupled with a flexible and cost-effective license model, additional cameras or functionality can easily be added at a later date without disruption to the existing system. What's more, there's no recurring support contracts to sign up to and technical support is free of charge.

## Wavestore's WaveView and WaveView Mobile clients

WaveView is Wavestore's free of cost client software which delivers an intuitive interface designed to offer full, yet simple, control of total security solutions. Authorised WaveView client devices can simply access individual or grouped Wavestore video servers and NVRs to give users full control of their security system.

The WaveView Mobile application adds mobile viewing capability enabling operators to view and control their system from iOS or Android devices.

WaveView's leading search and playback capabilities allow operators to quickly review recorded images via an intuitive play bar, providing instantaneous access to exactly the right image from any point in time from the recorded data, even over large amounts of stored data.

## Export of video evidence

In just three mouse clicks, operators can export clips from multiple cameras simultaneously to a variety of file formats or create a storyboard of events with a sequence of cameras, including virtual PTZ control of 360° fisheye cameras. Authentication and encryption of video and audio content are also supported.

## At a glance

### Camera channels

Up to 254 IP

### Hard drives

Up to 24 x 3.5"

### Storage capacity

Up to 240TB

### IP throughput

Up to 2,400Mbps/s

### PSU

Dual PSU as standard

### Failover ready\*

HyperRAID™ ready (up to N+5 redundancy)\*

EcoStore™ HDD spin-down ready\*

## Key Features

- Highly secure VMS embedded into the Linux Operating System (OS)
- Up to 4096bit encryption with comprehensive cyber-security package provided as standard
- Fully ONVIF conformant and truly open-platform
- Compatible with the world's leading camera brands and video formats
- Compatible with a wide range of camera technology including UHD, 4K, HD, 360° fisheye, panoramic, thermal, HD over analogue and analogue
- Comprehensive third-party integration capability across Intelligent Video Analytics, Access Control, Intruder Detection and other technologies\*

\* These features are available from the video server, NVR or HVR but are dependent on the Wavestore VMS channel license level to operate. Please check specifications prior to ordering.

\*\* Typical expected figures; please make sure the calculations for your specific camera and site requirements are completed before ordering.

TECHNICAL SPECIFICATION	X-Series
<b>Channels &amp; throughput</b>	
Max. IP channels	254
Max. built-in analogue channels	-
Max. audio channels	254
Max. IP throughput	1,200Mbps/sec (standard) 1,800Mbps/sec (option) 2,400Mbps/sec (option)
Compression formats	H.265, H.264, MJPEG, MPEG-4, MxPEG and JPEG2000
Typical video storage rate	1600 FPS
<b>Operation</b>	
Operating system	Linux (VMS embedded)
Operating system drive	64GB SATA DOM
CPU	Intel Xeon Family
RAM	16GB DDR4 ECC
Graphics card	On-board
<b>Connectivity</b>	
Network interfaces	4 x Gb NIC (standard) 6 x Gb NIC (option) 8 x Gb NIC (option)
USB ports	2 x USB 2.0 2 x USB 3.0
Monitor outputs	VGA
Alarm I/O module	Optional
Keyboard and mouse	Yes (not supplied)
<b>Wavestore VMS</b>	
Pre-installed with Wavestore's VMS	Yes
Wavestore VMS channel license compatibility	All levels
VMS configuration restore points	Yes
Multicast support	Yes
Automatic camera discovery and camera group set-up	Yes
<b>WaveView Client</b>	
Local client use	Setup only
Remote client use	Yes
WaveView Mobile compatible	Yes

**Popular configurations:**

- X424-32PU4-HR-4G-NA-D11**
- X424-80PU8-HR-6G-NA-D11**
- X424-240PU24-HR-8G-NA-D11**

4U rack-mount server, 32TB storage, 1,200Mbps, HyperRAID and EcoStore ready, dual PSU, 3-year warranty  
 4U rack-mount server, 80TB storage, 1,800Mbps, HyperRAID and EcoStore ready, dual PSU, 3-year warranty  
 4U rack-mount server, 240TB storage, 2,400Mbps, HyperRAID and EcoStore ready, dual PSU, 3-year warranty

**Build your X-Series Video Server:**

Series	Form Factor	Max No. of HDDs	Storage fitted (TB)	Drive type fitted	No. of HDDs fitted	RAID ports	No. of NICs	Analogue channels	Power supply	CPU options	Graphics options
X	4 (4U)	24	From 6TB to 240TB in multiples of 6TB, 8TB or 10TB	PU (Surveillance grade) GD (Enterprise grade)	1 to 24	HR (HyperRAID ready) R40 (4 int. 0ext.)	4G (4) 6G (6) 8G (8)	NA (none)	D (dual)	1 (standard)	1 (standard)

TECHNICAL SPECIFICATION	X-Series
<b>Storage and Hard Drives (HDDs)</b>	
Max. number of HDDs	24
Min. internal storage	6TB
Max. internal storage	240TB
HDD type	Surveillance grade (standard) Enterprise grade (option)
Hot swap HDD bays	Yes
EcoStore™ HDD spin-down compatible*	Yes
<b>Redundancy</b>	
RAID*	HyperRAID (RAID5/6, N+1/2) HyperRAID Plus (up to N+5)
Dual PSU	Yes
Failover compatible*	Yes
<b>Physical</b>	
Form factor	4U rackmount
Dimensions (D x W x H)	660mm x 483mm x 178mm
Weight (with 1 HDD fitted)	25.9kg (approx.)
Weight (each additional HDD)	Approx. 750g
Operating temperature range	5°C to 40°C 41°F to 104°F
Operating relative humidity (non-condensing)	20% - 80%
<b>Power</b>	
Power input	100-240v AC 50/60Hz
Power consumption with 1HDD	100W typical
Power consumption (each additional HDD)	9W typical
<b>Warranty</b>	
Standard warranty	3-year return to base
Extended warranty	Up to 5-years

**Rear Panel Connections:**

- VGA monitor connection (for set-up only)
- Network interface Ports 0,1,2,3
- 2 x 3.0 USB ports
- 2 x 2.0 USB ports
- Dual mains input

Channel licenses sold separately



Email: [info@wavestore.com](mailto:info@wavestore.com)  
 Visit: [wavestore.com](http://wavestore.com)

Specifications may change without notice.  
 Version: WST-0067-08

**GLOBAL HQ (EMEA)**  
 Wavestore Global Ltd.  
 Tel: +44 (0) 1895 527 127

**USA/CANADA**  
 Wavestore Americas Inc.  
 Toll-free: 855-526-8887

**MIDDLE EAST**  
 Wavestore Middle East  
 Tel: +971 (4)881 2903

