

Mercury™-based Wavestore Intelligent Controller

WS-MP4502

Key Benefits

Open Architecture:

High performance, reliable platform enables use of hardware with Mercury OEM partners' software solutions.

Enhanced Cybersecurity:

ARM TrustZone, secure boot CPU, crypto chip and data at rest encryption provide a layered security approach to protect sensitive data.

Edge Processing:

Advanced processing capabilities allow for custom applications to run in the controller, exponentially expanding the platform's processing possibilities at the edge.

Business Continuity:


New processor part of multi-year longevity program, dual footprint circuit designs and the same reliable LP/EP interface and footprint.

The new Mercury based Wavestore Ws-MP Intelligent Controllers provide a bridge between today's urgent security needs and tomorrow's emerging realities. Featuring Secure world processing within a trusted execution environment and a future-ready, on-device application environment to drive advanced enterprise strategies with sophisticated programs and analytics adjacent to the door. With unmatched cybersecurity, robust reliability, and an open architecture, the WS-MP controller infrastructure is ready for the challenges of today and well into the future.

The WS-MP4502 supports 2 million cardholder records and a variety of extended features including High Assurance Credential Authentication (pending firmware update) and complies with the BACnet/IP communication protocol. A USB to-Ethernet IP adapter provides a redundant host IP connection. It has direct hardware support for two openings and can scale to 64 access points. Built on proven Mercury hardware, this high-performance intelligent controller embeds elevator destination dispatch and provides integrated power management analytics to proactively detect failure before it occurs.

Built on the Mercury platform, the Wavestore intelligent controller can connect to cloud or server-based hosts and can operate independently to perform access control functions.

For partners seeking an empowering, comprehensive and open access control platform that is also reliable and cybersecure, the WS-MP4502 is the clear solution. It delivers a complete security and access control solution, an innovative edge processing and development environment, interoperability and data security.



Highlights

Security and Network

IPv4/v6

Host communications protected by TLS 1.2/1.3 or AES-256/128

Controller/IO Expansion connection protected by AES

Generate and load custom peer certificates for TLS

Port based network access control using 802.1X

FIPS 140-3 user of OpenSSL (in process)

Local Access Control Processing

Supports multiple card formats, paired and alternate readers, elevator, turnstile and biometric devices

Anti-passback support (area, reader and time based)

Programmable keypad user commands

Threat level and operating modes

Ability to power cycle each reader port individually

Third Party Integration Supported

Wireless Locks

FICAM Strong Authentication for FIPS-201 US Government (pending firmware update)

Elevator Destination Dispatch (pending firmware update)

Power Supply Alerts and Events

Building Control using BACnet/IP

Specifications

| WS-MP4502 Intelligent Controller | |
|----------------------------------|---|
| Access Control | 2,000,000 cardholder capacity 500,000 transaction buffer Supports up to 2 RS-485 IO protocols 255 access levels per cardholder Cardholder - 19 Digit (64 Bit) User ID with 15 digit PIN MAX Activation/Deactivation If/Then macro capabilities Anti-passback support Nested, area, hard, soft and timed forgiveness Adjustable cardholder capacity Supports up to 1024 inputs or 1024 outputs |
| Door Control | Natively supports up to 4 readers and 2 openings and can support up to 32 additional RS-485 expansion modules for a maximum of 64 readers and openings. |
| General | |
| Primary Power | 12-24 VDC +/- 10%, 550mA maximum (reader and USB current not included) |
| Reader Ports | 600mA maximum (add 600 mA to primary power current) |
| Micro USB Port | 5 VDC, 500 mA maximum (add 270 mA to primary power current) |
| Battery | Memory/Clock Backup: Super Capacitor (10 hours). 3 Volt Lithium, type BR/CR2032, slot available for additional capacity. Battery not included. |
| microSD Card | Format: microSD or microSDHC; 2GB to 8GB |
| Host Communication | Ethernet: 10Base T/100Base-TX and micro USB port (2.0) with optional adapter: pluggable model USB2-OTGE100 |
| Serial I/O Device | Two each, 2-wire RS-485, 2,400 to 115,200 bps, asynchronous, half-duplex, 1 start bit, 8 data bits, and 1 stop bit |
| Inputs | Eight unsupervised/supervised, standard EOL: 1k/1k ohm, 1%, ¼ watt. Two unsupervised dedicated for cabinet tamper and UPS fault monitoring. |
| Output Relays | Four relays, Form C, NO 5 A @ 30 VDC resistive, NC 3 A @ 30 VDC resistive |


| Reader Interface | |
|------------------|---|
| Reader Power | 12-24 VDC +/- 10% regulated, 600 mA maximum. |
| Data Inputs | TTL compatible inputs, F/2F or 2-wire RS-485 standards supported |
| RS-485 Mode | 9,600 to 115,200 bps, asynchronous, half-duplex, 1 start bit, 8 data bits, and 1 stop bit. Maximum cable length: 2000 ft. (609.6 m) |
| LED Output | TTL levels, high>3 V, Low<0.5 V, 5 mA source/sink maximum |
| Buzzer Output | Open collector, 12 VDC open circuit maximum, 40 mA sink maximum |

| Cable Requirements | |
|--------------------|---|
| Power and Relays | 1 twisted pair, 18 to 16 AWG |
| Ethernet | CAT-5, minimum |
| Reader TTL | 6-conductor, 18 AWG, 500 feet (150 m) maximum |
| Reader F/2F | 4-conductor, 18 AWG, 500 feet (150 m) maximum |
| I/O Devices RS-485 | 1 twisted pair, shielded, 24 AWG, 120 ohm impedance, 2,000 feet (610 m) maximum |
| RS-485 I/O Devices | 1 twisted pair, shield, 120 ohm impedance, 24 AWG, 4,000 ft. (1,219 m) maximum |
| Alarm Input | 1 twisted pair, 30 ohms maximum, typically 22 AWG @ 1000 ft. (304.8 m) |

| Environmental | |
|---------------|---|
| Temperature | Storage: -55° to 85°C Operating: 0° to 70 °C |
| Humidity | 5 to 95% RHNC |

| Mechanical | |
|------------|--|
| Dimensions | 8.0 in. (203mm) W x 6.0 in. (152mm) L x 1.0 in. (25mm) H |
| Weight | 10.65oz (302 g) nominal, board only |

| Compliance and Warranty | |
|-------------------------|---|
| Product Compliance | UL294 Recognized, FCC Part 15 Class A, CE Compliant, RoHS (2011/65/EU & 2015/863), EU REACH (1907/2006), California Proposition 65, NIST Certified Encryption (in process) |
| Warranty | The product is warranted free from defects in material and workmanship under normal use and service with proper maintenance for one year from the date of factory shipment. |



Visit wavestore.com/wavefusion for more information.

Wavestore Global Ltd
0800 640 6660
info@wavestore.com

Wavestore Canada Inc
+1 855 526 8887
salesamericas@wavestore.com

Wavestore Middle East
+971 (4)881 2903